

## VS82

2-Port VGA Splitter Wall Plate (Plastic) (250MHz)



The VS82 Video Splitter duplicates the video signal from an input source (i.e. a computer) and route it to up to 2 display devices (monitors, projectors, etc.). However, they go beyond being merely duplicators, in that they also enhance the video signals over distances up to 30 meters. Furthermore, they can be cascaded three levels to additional ATEN video splitters to support many numerous display devices. And they mount inconspicuously on the wall or out of sight.

### Features

- One video input to 2 video outputs.
- Cascadable to 3 levels - provides up to 8 video signals.
- Supports up to 250 MHz bandwidth.
- Long distance transmission - up to 30 m (210') . \*
- High video resolution - up to 1920 x 1440.
- DDC, DDC2, DDC2B Compatible (Port 1 only).
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall.
- Supports VGA, XGA, SVGA, UXGA and multisync monitors.
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun

\* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.

## Specifications

|                        |                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Input            |                                                                                                                                                                                                                                                                                                           |
| Interfaces             | 1 x HDB-15 Male (Blue)                                                                                                                                                                                                                                                                                    |
| Max. Distance          | 1.8 m                                                                                                                                                                                                                                                                                                     |
| Impedance              | 75 $\Omega$                                                                                                                                                                                                                                                                                               |
| Video Output           |                                                                                                                                                                                                                                                                                                           |
| Interfaces             | 2 x HDB-15 Female (Blue)                                                                                                                                                                                                                                                                                  |
| Impedance              | 75 $\Omega$                                                                                                                                                                                                                                                                                               |
| Video                  |                                                                                                                                                                                                                                                                                                           |
| Max. Bandwidth         | 250 MHz                                                                                                                                                                                                                                                                                                   |
| Max. Resolution        | Up to 1920 x 1440                                                                                                                                                                                                                                                                                         |
| Max. Distance          | Up to 30 m                                                                                                                                                                                                                                                                                                |
| Connectors             |                                                                                                                                                                                                                                                                                                           |
| Power                  | 1 x DC Jack                                                                                                                                                                                                                                                                                               |
| Power Consumption      | DC9V:1.02W:5BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental          |                                                                                                                                                                                                                                                                                                           |
| Operating Temperature  | 0-50°C                                                                                                                                                                                                                                                                                                    |
| Storage Temperature    | -20 - 60°C                                                                                                                                                                                                                                                                                                |
| Humidity               | 0 - 80% RH, Non-Condensing                                                                                                                                                                                                                                                                                |
| Physical Properties    |                                                                                                                                                                                                                                                                                                           |
| Housing                | Plastic                                                                                                                                                                                                                                                                                                   |
| Weight                 | 0.14 kg ( 0.31 lb )                                                                                                                                                                                                                                                                                       |
| Dimensions (L x W x H) | 8.76 x 11.46 x 3.33 cm<br>(3.45 x 4.51 x 1.31 in.)                                                                                                                                                                                                                                                        |
| Carton Lot             | 20 pcs                                                                                                                                                                                                                                                                                                    |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.                                                                                                                                                                           |

**Diagram****ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.