

2L-7D03DP-1

3 m DisplayPort rev.1.4 Cable



The ATEN DisplayPort rev.1.4 Cable supports 32.4 Gbps data rate with high-definition connectivity and advanced auxiliary channeling. It is a professional connection of your DisplayPort supported (gaming) PC, use in conjunction with ATEN DisplayPort solutions, laptop to an ultra high resolution monitor, or other DisplayPort interface devices. Our DisplayPort rev.1.4 Cable allows for up to 8K Dynamic HDR with 32 channels for high quality video and audio experience. Each connector features latches that provide a secure connection with a release button.



Features

- Crystal-clear video up to 8K (7680 x 4320 @ 60Hz), backward compatible with 5K (5120 x 2880 @ 60Hz) and 4K (4096 x 2160 @ 120Hz) and previous generations of DP
- High Bit Rate 3 (HBR3) bandwidth of 32.4 Gbps
- Multi-Stream Transport (MST) for daisy-chaining multiple monitors
- Forward Error Correction
- Display Stream Compression (DSC)
- 32 uncompressed digital audio channels
- RoHS compliant

Specification

Max. Video Resolution	Up to 7680x4320@60Hz
Physical Properties	
Cable Length	3M
Cable Color	Black
Cable Outer Dimension	8.0 ± 0.2mm
Conductor Gauge	26AWG
Conductor Material	Tinned Copper
Connector Plating	Nickel
Connector Type	DisplayPort (20 pin) Male to Male
Cable Shield Type	Aluminum Magnesium Alloy
Cable Jacket Type	PVC
Environmental	
Operating Temperature	80°C
Rating	UL VW-1 (Flame rate), CSA

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.