

## 2L-5205B

5M Port Switching VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. Featuring durable design, the cable eliminates the picture ghosting and fuzzy images, guaranteeing users a reliable signal transmission. For application utility, the VGA cable is compatible with ATEN KVM switches to change KVM port focus.

### Features

- Optimized for analog signal transmission at resolution up to 1920 x 1200
- VGA cable with 15-pin female input and male output
- Audio supported
- Outer shielded with Al Mylar tape for reliable signal transmission
- RoHS compliant
- Tested for compatibility with ATEN VGA KVM products

**Specification**

|                        |                          |
|------------------------|--------------------------|
| Cable Length           | 5m                       |
| Switches               |                          |
| Port Selection         | Port Switching Button    |
| Shield                 |                          |
| Material               | AL-Mylar                 |
| Jacketed               |                          |
| Material               | PVC (PolyVinyl Chloride) |
| Conductor              |                          |
| Conductor Diameter     | 30 AWG                   |
| Material               | Tinned copper            |
| TO Switch Interface    |                          |
| Mini Stereo Jack       | Audio Plug (Speaker)     |
| KVM Port               | HDB-15 Female            |
| TO PC/Source Interface |                          |
| VGA                    | HDB-15 Male              |
| Mini Stereo Jack       | Audio Plug (Speaker)     |

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.