

BC24V9AH

Internal Battery Pack for OL1000LV / OL1000HV



The ATEN UPS Internal Battery Pack comes with a hot-swap design, allowing uninterrupted operations during battery replacement to ATEN UPS systems. It ensures stable power supply and offers easy installation, bringing users hassle-free management to their power equipment.

Note: When the battery pack is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.

Specification

Electrical	
Nominal Output Voltage	24V
Battery	
Battery Type	Sealed Lead-Acid
Battery Size	9Ah
Battery Quantity	2
Physical Properties	
Dimensions (L x W x H)	25.77 x 21.37 x 6.66 cm (10.15 x 8.41 x 2.62 in.)
Weight	5.70 kg (12.56 lb)
Color	Black
Environmental	
Temperature (Operating / Storage)	Operating: 32 – 104 °F (0 – 40 °C) Storage: -15 – 45 °C
Humidity (Operating & Storage)	0–95%
Elevation (Operating / Storage)	Operating: 0-10,000ft (0-3,000meter) Storage: 0-50,000ft (0-15,000meter)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.