

KA9250

PS/2 VGA 콘솔 연장기 (KH0116 전용 콘솔 모듈)



The KA9250 KVM Extender Module allows a user at a keyboard, video, mouse (KVM) console to manage the servers in a [KH0116](#) 16 Port High-Density KVM Switch installation up to 150m away. The KA9250 module connects to the [KH0116](#)'s RJ-45 remote console port via standard Category 5 cable for a neat and reliable installation. When a local and remote console are present, both can access the KVM switch.

The KA9250 features a custom ASIC to ensure the utmost in reliability and compatibility. It can also sense the distance to the [KH0116](#) and automatically adjust the video gain to compensate. Control your KVM switch from up to 150m away by extending the distance to your KVM console with a KA9250 KVM Extender.

특장점

- Built-in ASIC for greater reliability and compatibility
- Cat 5e cable to connect the remote unit to the [KH0116](#) up to 150m away
- High resolution video-up to 1280 x 1024 (SXGA)
- Supports VGA, SVGA, and MultiSync monitors
- Automatic gain control-adjusts signal strength to compensate for distance
- Multiplatform support: Windows 2000/XP/[Vista](#).

사양

커넥터	
링크	1 x RJ-45 Female (Black)
컴퓨터	1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDB-15 Female (Blue)
LED	
온라인	1 (Green)
전원	1 (Orange)
비디오	1280 x 1024
케이블 길이	150m
소비 전력	AC 9V 4.0W (max.) 노트: ● 와트 단위의 측정은 외부 부하가 없는 장치의 일반적인 전력 소비를 나타냅니다. ● BTU/h 단위의 측정값은 장치가 완전히 로드되었을 때 장치의 전력 소비를 나타냅니다.
사용 환경	
사용 온도	0 ~50°C
보관 온도	-20 ~60°C
습도	0 ~ 80% RH, Non-condensing
제품 외관	
재질	Metal
무게	0.22 kg
크기 (L X W X H)	10.10 x 8.68 x 3.88 cm
노트	일부 랙 마운트 제품은, WxDxH의 표준 물리적 치수를 LxWxH 형식으로 사용하고 있습니다.

다이어그램



에이텐 코리아 ATEN KOREA

서울시 금천구 디지털로9길 32(가산동) 갑을그레이트밸리 B동 303호

Tel: 02-467-6789 Fax: 02-467-9876

www.aten.com/kr/ko E-mail: marketing@aten.co.kr



© Copyright 2025 ATEN® International Co., Ltd.
ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.