

2L-2503

3M VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate A/V experiences.

Features

- Optimized for analog signal transmission
 - VGA cable with 15-pin male input and output
 - Bend Radius: 60°*
 - Outer shielded material: Al Mylar tape
 - Compatible with ATEN VGA products
- Note:* Swings 3000 times between angles of +/- 60 degrees, at a frequency of 40 times per minute

Specifications

Conductor	
Material	Tinned Copper
Conductor Diameter	30 AWG
Jacketed	
Material	Jacket: PVC Shielding: AL-Mylar
Connectors	
Video	HDB-15 Male HDB-15 Male
Cable Length	3 m



Simply Better Connections

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.